

# LED PANEL 2X2 20/30/35W 3CCT



## Specifications

Item	- 36657A
Model	- LED PANEL 2X2 20/30/35W 3CCT
Bulb Type	- LED
Input Voltage	- 120-277V 60Hz
Watts	- 20W/30W/35W
PF	- >0.9
Dimmable	- Yes (0-10V)
Beamspread	- 120°
Color Temp	- CCT Selectable (35K, 4K, 5K)
CRI	- 80
Lumen	- 2,200/3,300/4,000
Average Life Hours	- 50,000
Location Rating	- Dry/Damp
Ambient Operating Temp	- -4°F to 113°F (-20°C to 45°C)
Surge Protection	- 2KV
Length	- 23.75" (603 mm)
Width	- 23.75" (603 mm)
Height	- 1.7" (43mm)
	- Type IC

## Caution

- This fixture must be wired in accordance with the National Electrical Code and applicable local ordinance. Proper grounding is required to insure personal safety. Carefully observe grounding procedure under installation section.
- Make certain power is OFF before starting installation or attempting any maintenance. Risk of fire/electric shock. If not qualified, consult an electrician.
- Disconnect power at fuse or circuit breaker before installing or servicing
- Risk OF BURN--Disconnect power and allow fixture to cool before servicing.
- RISK OF PERSONAL INJURY--Fixture may become damaged and/or unstable if not installed properly. Tighten all fixture components to their recommended torque values.



Dimmable

