

# LED GARAGE LIGHT

## Specifications



Item	- 37325A
Model	- LED GARAGE LIGHT
Bulb Type	- LED
Beam Spread	- 120°~270° Adjustable
Input Voltage	- 120-277VAC 50/60Hz
Watts	- 65W
Base Type	- E26
Color Temp	- 5000K
CRI	- >80
Lumen	- 8000
Dimmable	- No
UL Rating	- Suitable for Dry/Damp Locations
Life	- 25,000 Hours
Ambient operating temp	- -40°F to 104°F (-40°C to 40°C)
Diameter	- 10.75" (273.0 mm) unfolded
Length	- 3.75" (95.3 mm) unfolded
Finish	- Black
Surge Protection	- 2KV
	- Not suitable for use in enclosed fixtures.

## Caution

- When using product, basic precautions should always be followed.
- Read and follow these instructions and observe all warnings.
- Carefully read and understand the information given in this manual before beginning installation. Failure to do so could lead to electric shock, fire, or other injuries which could be hazardous or even fatal.
- Save these instructions and warnings

**This product may present a possible shock or fire hazard if improperly installed or mounted. Products should be installed following these instructions, local electrical codes, and the current National Electric Code (NEC).**

## Warning

**To avoid risk of electrical shock, shut off power before installing or servicing this product.**

**NEVER submerge this product in water!**

- Do not install this product in places where water accumulates.
- Do not use on hot surfaces.
- Do not remove the lens which protects the LED chips.
- Do not use this product in areas near a gas source.
- Do not change the LED light source.
- Do not use this product in potentially explosive environments.
- This product is NOT A TOY and is not suitable for use by children.
- Do not dismantle this product. There are NO replaceable LEDs or serviceable parts.
- Suitable for fixtures rated for temperatures ranging from -40°F to 104°F.
- NOT Suitable for enclosed fixtures.
- Do not use this product where exposed to standing water.
- Do not expose bare wires outside of the electrical connections.
- Make sure wiring section is insulated.
- DO NOT USE WITH DIMMERS. This product is not suitable for any sort of dimmer.
- Using this product with any sort of dimmer will void the warranty.



**Installation Instructions**

1. Before installing the bulb, shut off power supply at the circuit breaker panel to avoid electrical shock. It is recommended that surge/lightning protection be installed. Ballast must be bypassed if present. After the modification is complete, attach the modified luminaire label to a visible place on the fixture.
  2. Remove old bulb.
  3. Screw new bulb in clockwise. Do not overtighten. Overtightening may cause damage to the light.
  4. Individually pivot each of the adjustable panels down to best cover the desired space. Depending on the type of light fixture, it may be necessary to pivot light heads out of the way before screwing the bulb into the fixture.
  5. Restore power.
  6. Turn on light switch. Bulb will illuminate immediately.
  7. Adjust all angles as needed.
- (Do not stare directly into LED lights when adjusting settings.)



**Troubleshooting Guide**

Problem	Probable Cause	Solution
Fixture does not turn on.	Bad connection.	Check wiring connections.
	Faulty switch.	Test switch or replace it.
	Power is off.	Verify power supply is on.
Circuit breaker trips or fuse blows when light is turned on.	Discontinue use immediately.	Call an electrician.

**Cleaning Instructions**

1. Turn power OFF.
  2. Use a soft cloth and a mild, non-abrasive glass cleaner.
  3. Lightly wipe and clean the fixture.
- DO NOT use solvents.  
DO NOT use cleaners containing abrasive ingredients.  
NEVER spray cleaning liquid directly onto the LEDs, fixture, or wiring.

**EYES**



- Do not look directly at LEDs for extended periods of time.
- Do not shine the light directly into other people's eyes.

**Installation Diagram**

