

38677A	LED33T8/835/8FT/DR/SS FA8	33W	35K	4400 Lumens
38678A	LED33T8/841/8FT/DR/SS FA8	33W	41K	4400 Lumens
38679A	LED33T8/850/8FT/DR/SS FA8	33W	50K	4400 Lumens
38680A	LED33T8/865/8FT/DR/SS FA8	33W	65K	4400 Lumens

## LED Fluorescent Direct Replacement

50,000 Avg Life Hours

4400 Initial Lumens

Direct Replacement

Fa8 Single Pin Base Type

T8 Bulb Shape

3500-6500K Kelvin

82 CRI

33 Watts

120-277 Volts

Beamspread 120°

Safe-Shield<sup>®</sup>



- LONG LIFE
- ENERGY EFFICIENT
- ROHS COMPLIANT
- NO MERCURY NO LEAD
- ZERO UV DYE AND PIGMENT FADE
- 3000 - 6500K 82 CRI.
- UL CERT DR.
- 96 in. NOMINAL LENGTH.
- NOT FOR OUTDOOR USE.
- MIN. AMBIENT OPERATING TEMP. -4°F. -20°C.
- MAX. AMBIENT OPERATING TEMP. 113°F. 45°C.
- NOT COMPATIBLE WITH LOW POWER FACTOR BALLASTS
- DESIGNED TO RUN ON INSTANT START AND PROGRAMMED START BALLASTS.



Diameter:  
1.18 in.  
(29.97 mm.)

Max Overall Length: 93.75 in. (2,381.25 mm.)

